

[illegible]



Dump Body 1/4" Floor
stroked

Quote WTTLLC00006336

Page 1 of 2
Date 10/11/2015

Warren Truck and Trailer, LLC
15768 US HIGHWAY 271 NORTH
Talco TX 75487

Phone (888) 734-4400
Fax (903) 379-4400
WarrenTruckAndTrailer.com

Bill To	Ship To	Contact
MHC KENWORTH 4040 IRVING BLVD DALLAS TX 75247	MHC KENWORTH 4040 IRVING BLVD DALLAS TX 75247	(214) 920-7300 Ext. 0000

Purchase Order No.		Customer ID	Salesperson ID	Shipping Method	Payment Terms	Req Ship Date	Master No.
		MHC247	MACK	DELIVERED	NET30	0/0/0000	10,010,455
QTY	Item Number	Description	UOM	Unit Price	Ext. Price		
1	U-10	DUMP BODY - UNDERBODY - 10' C/O GRAND PRAIRIE Yardage: 5/6 Floor Material: 1/4" A1011 Front / Material: 30" 10 GA A1011 Side / Material: 24" 10 GA A1011 Vertical Side Brace: Yes Horizontal Brace: No Hoist / Cylinder: U50-723 Hydraulics: Yes	EA	\$11,980.00	\$11,980.00		
1	TAILGATE	Air Operated: Yes Panel: 3 Vertical Material: 10 GA A1011 Height: 30 Slope: None Chains: 5/16" Double Acting: Yes	Each	\$0.00	\$0.00		
1	DB OPTIONS # 1	Cabshield: Full Width x 1/2 (24") Asphalt Apron: No Bolt On: No Body Lights: LED Yes (Rubber Mounted) Oval S/T/T: (1) Per Each Rear Post	Each	\$0.00	\$0.00		
1	INSTALL	Hydraulic Hoses/Fittings: Yes Pump: 22 gal w/air shift CW (400-80263) Console: Clutch Shift Air Conspicuity Tape: No Mudflaps and Brackets: Yes (NO LOGO) NO WARREN DECALS Side Boards: Formed Metal -2x6x3/16 Delivery Fuel/Charges: Yes	Each	\$0.00	\$0.00		
1	PAINT	Color: WARREN STOCK COLOR	Each	\$0.00	\$0.00		
1	PTO	POWER TAKE OFF PTO Muncie CS Series (Auto)	EA	\$0.00	\$0.00		



Quote WTTLLC00006336

Page 2 of 2
Date 10/11/2015

Warren Truck and Trailer, LLC
15768 US HIGHWAY 271 NORTH
Talco TX 75487

Phone (888) 734-4400
Fax (903) 379-4400
WarrenTruckAndTrailer.com

Purchase Order No.		Customer ID	Salesperson ID	Shipping Method	Payment Terms	Req Ship Date	Master No.	
		MHC247	MACK	DELIVERED	NET30	0/0/0000	10,010,455	
QTY	Item Number	Description				UOM	Unit Price	Ext. Price
1	SAFETY LIGHTING	2) WHELEN AMBER LED "CORNER STROBES" MOUNTED IN FRONT GRILLE, ONE EACH SIDE (2) 6" OVAL AMBER LED STROBES RUBBER MOUNTED, (1) IN EACH REAR CORNER POST 24" LED AMBER LIGHT BAR MOUNTED ON CAB PROTECTOR				Each	\$0.00	\$0.00
1	ADDITIONAL SPECS.	NO LOGOS ON MUDFLAPS OR BODY BODY LADDER- D/S (ANTI-SKID RUNGS WITH BOTTOM RUNG APPROX. 28" BELOW BODY) ALL BODY LIGHTS TO BE RUBBER MOUNTED METAL CLAD REFLECTORS ON BODY SIDES AND REAR ALL BODY WIRING WITH CRIMPED CONNECTORS AND IN SPLIT LOOM				Each	\$0.00	\$0.00
1	DELIVERY	DELIVERY OF COMPLETED UNIT TO MHC-DALLAS. DELIVERY CHARGES SHOWN IN SHIPPING COLUMN BELOW				Each	\$0.00	\$0.00

Quotation reviewed and accepted by:
(signed) _____
Please fax back to us for entry as an order
NOTE: Quotation good for 10 days only

Subtotal	\$11,980.00
Misc	\$0.00
Tax	\$0.00
Ship & Handling	\$300.00
Trade In Allowance	\$0.00
Total	\$12,280.00

Pin the Airch \$10,50
Air + Electric
\$13,330.00



MHC Kenworth-Dallas T180
4040 IRVING BLVD.

CITY OF GRAND PRAIRIE
EQUIPMENT SERVICES
1821 W. FREEWAY

DALLAS, Texas United States 75247
Phone: (214) 920-7300
Fax: (214) 920-7316
Email: randy.smartt@mhctruck.com

GRAND PRAIRIE, Texas United States 75053
Phone: (972) 237-8270
Fax:
Contact Email:
Prepared for: Jayson Ramirez

Vehicle Summary

Unit		Chassis	
Model:	T300 Series Conventional.	Fr Axle Load (lbs):	10000
Type:	FULL TRUCK	Rr Axle Load (lbs)	21000
Description:	6-8 YRD Dump	G.C.W. (lbs):	31000
Application		Road Conditions:	
Intended Serv.:	Local pickup & delivery.	Class A (Highway)	89
Commodity:	Vehicles which haul	Class B (Hwy/Mtn)	10
	Gravel/crushed rock/sand	Class C (Off-Hwy)	01
Body		Class D (Off-Road)	00
Type:	End dump	Maximum Grade:	6
Length (ft):	10.0	Wheelbase (in):	177
Height (ft):	12.0	Overhang (in):	63
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):	68
Trailer		Cab to Axle (in):	109
No. of Trailer Axles:	0	Cab to EOF (in):	172
Type:		Overall Comb. Length (in):	281
Length (ft):	0.0	Special Req.	
Height (ft):	0.0	U.S. Domestic Registry, 50-State	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	120		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.

Printed: 10/30/2015 2:25:41 PM
 Effective Date: Jul 1, 2015
 Prepared by: Randy Smartt

Complete

Model Number: T300 Series Conventional
 Quote/DTPO/CO: Q81518427
 Version Number: 36.22



MHC Kenworth-Dallas T180
 4040 IRVING BLVD.

CITY OF GRAND PRAIRIE
 EQUIPMENT SERVICES
 1821 W. FREEWAY

DALLAS, Texas United States 75247
 Phone: (214) 920-7300
 Fax: (214) 920-7316
 Email: randy.smartt@mhctruck.com

GRAND PRAIRIE, Texas United States 75053
 Phone: (972) 237-8270
 Fax:
 Contact Email:
 Prepared for: Jayson Ramirez

Model	Description	Weight
	T300 Series Conventional.	9,764
	Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floormat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	
	T370 Class 7: medium-duty Conventional.	0
	Chassis operation will not include a stationary application. Stationary operation is defined as running the engine under load while stationary at a substantial fraction of engine gross horsepower (60% or greater) for an extended period of time (longer than 5 - 10 minutes).	0
	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
	Medium-duty 4x2 automatic.	0
	Gravel/crushed rock/sand	0
	Local pickup & delivery. Vehicles which haul freight, typically operating within a 100-mile radius, on public streets & highways, & other paved surfaces, including limited Class C roads. Includes package & freight delivery, as well as fuel oil or petroleum distribution, etc. Road usage: minimum 3% Class B, do not code for Class D.	0
	End dump	0
	U.S. Domestic Registry, 50-State	0

Engine & Equipment

PACCAR PX-7 240 2013 240@2400 235@2600 560@1600.	0
Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing.	
N09200 N205 120...Standard Maximum Speed Limit [LSL]	
N09220 N207 0....Expiration Distance	
N09240 P09 120...Hard Maximum Speed Limit	
N09260 P14 66...Maximum Accelerator Pedal Vehicle Speed	
N09280 P16 0....Accelerator Lower Droop	
N09300 P19 66...Maximum Cruise Speed	
N09320 C143 0....Cruise Control Lower Droop	
N09360 N203 252...Reserve Speed Function Reset Distance	
N09380 N202 0....Maximum Cycle Distance	

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 10/30/2015 2:25:41 PM
Effective Date: Jul 1, 2015
Prepared by: Randy Smartt

Complete

Model Number: T300 Series Conventional,
Quote/DTPO/CO: Q81518427
Version Number: 36.22



Description	Weight
N09420 N201 0...Reserve Speed Limit Offset	
N09440 P11 Yes...Engine Protection Shutdown	
N09460 P06 No...Gear Down Protection	
N09480 P26 1400.Max PTO Speed	
N09500 P02 No...Cruise Control Auto Resume	
N09520 P04 No...Auto Engine Brake in Cruise	
N09540 N209 0...Expiration Distance	
N09560 P520 Yes...Enable Idle Shutdown Park Brake Set	
N09580 P32 5...Timer Setting	
N09600 P233 Yes...Enable Impending Shutdown Warning	
N09620 P234 60...Timer For Impending Shutdown Warning	
N09640 P516 35...Engine Load Threshold	
N09680 P33 No...Idle Shutdown Manual Override	
N09720 P230 Yes...Enable Hot Ambient Automatic Override	
N09740 P46 40...Low Ambient Temperature Threshold	
N09760 P56 60...Intermediate Ambient Temperature Threshold	
N09780 P47 80...High Ambient Temperature Threshold	
Prospector version 36.1	
Supersedes previous version 36.02	0
Effective VSL Setting NA	0
Engine Idle Shutdown Timer Disabled	0
Eff EIST NA Expiration Miles	0
Use only with MX and Cummins engines	
Air compressor: Cummins 18.7 CFM, Cummins, PACCAR	0
PX engines.	
Air Cleaner: Dry-type firewall mounted w/filter	0
restriction indicator.	
Fan Hub: Horton On/Off for PX-7	0
Cooling module: 1000 square inches	0
T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	
RH under cab SCR for PX-6 / PX-7 w/ single	88
vertical RH SOC tailpipe.	
Tailpipe: 5 in. single 24 in. 45 degree curved.	-2
Fuel filter PACCAR PX-7 engines	0
and Cummins ISB Euro 3 Unheated.	
Alternator: PACCAR 160 amp, brush type	0
Batteries: 2 PACCAR GP31 threaded post (700) 1400	0
CCA dual purpose.	
12-VOLT LIGHT SYSTEM W/CIRCUIT PROTECTION	
Starter: PACCAR 12 volt electrical system. W/	0
centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	
Multi-function engine connector for body builder	0
interface for Cummins.	

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 10/30/2015 2:25:41 PM
 Effective Date: Jul 1, 2015
 Prepared by: Randy Smartt

Complete

Model Number: T300 Series Conventional
 Quote/DTPO/CO: Q81518427
 Version Number: 36.22



Description	Weight
Transmission: Allison 2500RDS 5-speed w/PTO drive gear, 5th Gen controls. Includes heat exchanger. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	48
Driveline: 2 SPL100 1 centerbearing light duty.	27
Torque converter included w/Allison Transmission.	0
Delete Allison FuelSense	0
Front Axle & Equipment	
Dana Spicer E-1002I Front Axle rated 10K 3-1/2in. drop.	-34
Front brakes included w/ front hub package.	0
Air Brake: 14,600 lb. package includes Bendix 16-1/2 x5 brakes, cast drums, aluminum 10-bolt hub pilot LMS hubs, hubcaps, oil seals & automatic slack adjusters. For use w/ 22-1/2in. wheels.	0
Front Springs: Taperleaf 12K w/ shock absorber for use on 2010+ chassis w/ 22.5in. wheels only.	12
Single power steering gear: 13.2K for air brakes.	0
Rear Axle & Equipment	
Single Meritor MS21-14x4 rear axle rated at 21K.	16
Rear Axle Ratio - 5.29.	0
Single rear brakes included w/rear hub package.	0
23K air brake package includes 16-1/2x7 in. brakes, cast drums, aluminum 10-bolt hub pilot LMS hubs, automatic slack adjusters and oil seals for use w/ 22.5 in. wheels.	0
Spring Brake: 3030 high output single.	0
Bendix 4S/4M anti-lock brake system.	0
Rear suspension: single Reyco 79KB taperleaf 21K. Medium-duty. Unladen Height: 9 in. Laden Height: 7.5 in. Not rear air disc brake compatible.	0
Heavy-duty rear suspension crossmembers for Reyco 79KB replacing T3 standard.	41
Tires & Wheels	
Front tires: Goodyear G661 HSA 11R22.5 16PR. 41.8 in. diameter, all position. 19.5 in. SLR.	16

Rear tires: Goodyear G572A LHD Fuel Max 11R22.5
14PR, 42.4 in. diameter, 19.9 in. SLR, Drive tire. Smartway certified. Code
is priced per pair of tires.

Rear Tire Quantity: 4

Front wheel: Accuride 50344 22.5x8.25 steel
Steel Armor(TM) powder coat, hub pilot mount, heavy-duty 5 hand-hole
hub pilot mount.

Rear wheel: Accuride 50344 22.5x8.25 steel
Steel Armor(TM) powder coat, hub pilot mount. Heavy-duty 5 hand-hole
hub pilot mount. Code is priced per pair of wheels.

00
0
20
40

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2015 2:25:41 PM	Complete	Model Number:	T300 Series Conventional.
Effective Date:	Jul 1, 2015		Quote/DTPO/CO:	Q81518427
Prepared by:	Randy Smartt		Version Number:	36.22



	Description	Weight
	Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
	Rear Wheel/Rim Quantity: 4	0
Frame & Equipment		
	Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel to 284 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	274
	Bumper: Aerodynamic, Painted. Requires a bumper setting code.	0
	40.9 in. Bumper setting. Requires a bumper code.	0
	Removable Front Tow Hooks: 2.	15
	Front mudflaps.	0
	Battery box cantilever aluminum BOC w/ fiberglass cover.	0
	Battery box location: LH Side.	0
	T270/370 Non-polished 2010 or later DPF/SCR cover with cab access step assembly, RH under.	0
	One bolted rear cab crossmember: Replacing T3 standard.	17
	Square end-of-frame w/ crossmember; non-towing.	41
Fuel Tanks & Equip		
	Fuel Tank: 56 US gallon 24.5in. aluminum under replace.	-45
	Small round DEF tank. 11 gallons of useable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
	Standard DEF to fuel fill ratio: 2:1 or greater.	0

DEF tank location is on the LH.

0

Location: 56 gal fuel tank LH under cab

0

Cab & Equipment

Cab: Curved Glass Conventional.

0

Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 10/30/2015 2:25:41 PM
Effective Date: Jul 1, 2015
Prepared by: Randy Smartt

Complete

Model Number: T300 Series Conventional.
Quote/DTPO/CO: Q81518427
Version Number: 36.22



Description	Weight
Hood: Sloped aerodynamic hood includes grill & separate bumper.	0
Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control, T660 include filter media.	0
Adjustable telescoping tilt steering column.	10
5 sets of keys. Replaces standard 2 sets of keys.	0
Switch & Wiring for Customer-Installed PTO. Electric over hydraulic PTO. Includes switch guard. Wiring is routed to LH frame for connection to the customer installed PTO. No air controls are provided with this code.	0
Two spare switches: Wired to power.	0
Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
Cab interior: Pinnacle. Includes vinyl headliner & cab back panel, slate gray interior, dark slate gray seats, floormats, LH/RH inside sunvisor & door courtesy lights.	0
Driver seat: Kenworth Air cushion Plus IB vinyl. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6-23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
Rider seat: Kenworth Toolbox Plus IB vinyl. W/dual armrests.	-4
Kenworth Radio with AM/FM/WB/USB and Bluetooth	4
Self cancelling turn signal: W/head light dimmer	0

Cab access contoured grabhandles, LH/RH.	0
DAYLITE DOOR: LH/RH INCL RH PEEPER WINDOW	0
Single rectangular air horn 23 in. LH top of roof Includes air horn cover.	6
Dual convex mirror 8.5 inch w/ offset mounting below regular mirror, and non-heated.	0
Single convex mirror 8-1/2 in. x 4-7/16 in. located on rider side, and non-heated.	0
Mirror: Dual Prutsmann mirror 7 in. x 16 in. polished stainless steel, thermostatically controlled. switch located on door pad.	0
Mirror brackets 8-1/2 ft load width.	0
Rear Cab Stationary Window 17 in. x 36 in.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2015 2:25:41 PM	Complete	Model Number:	T300 Series Conventional.
Effective Date:	Jul 1, 2015		Quote/DTPO/CO:	Q81518427
Prepared by:	Randy Smartt		Version Number:	36.22



Description	Weight
Manual LH & electric-powered RH door window. Switch located on door.	0
Lights & Instruments	
Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0
Marker Lights: Five, rectangular, LED	0
Turn Signal Lights: Mounted on fender	0
Turn Signal Flasher: Kysor solid state.	0
Switch & Wiring for Customer-installed Floodlight w/o electrical pass-through - 1st set. Wire coiled BOC/BOS.	0
Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
Switch & Wiring: Customer-installed dual beacon lights w/o insulators. Coiled wire behind dash.	1
Electric Backup Alarm: Meets SAE J994 & OSHA requirements.	4
Wiring:Cust. Install Trlr Elec. Brake Controller Class 8 Content: 7 Way plug wired to dash. Center pin of standard 7 Way J560 will be wired to the connector near the steering wheel. This option includes the following signals: Ignition, Ground, Stop Lamp and Center pin. This option is available when an additional 7 way connector is specified. A second trailer connection is required with ABS. Medium Duty Content: 2 Way Deutsch connector in chassis wired to dash with the following signals: Ground and Trailer Brake Controller wire from the cab. MP 280 Series connector in dash includes Battery, Ground, Stop Lamp Signal and Trailer Brake Controller wire from chassis.	1
Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Breakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat,	0

gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.

Air Equipment

Air Dryer: Bendix AD-IS heated.	0
Full truck kit: Gladhands mounted at end-of-frame. Seven-way female receptacle mounted at end-of-frame in taillamp bracket. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve, tractor protection valve, and spring brake inversion/relay valves are standard.	15
Trailer ABS electric supply through SAE J560 7-pin connector per TMC RP137).	0

Extended Warranty

Medium-duty Warranty: 1-year/unlimited mi.	0
---	---

Miscellaneous

GHG Secondary Manufacturer: Does Not Apply	0
---	---

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/30/2015 2:25:41 PM	Complete	Model Number:	T300 Series Conventional.
Effective Date:	Jul 1, 2015		Quote/DTPO/CO:	Q81518427
Prepared by:	Randy Smartt		Version Number:	36.22



Description	Weight
Additional lead time required for off highway & /or specialty component truck.	0
Warning triangle reflector kit: Shipped loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	4
One 5 lb. dry chemical type fire extinguisher mounted outboard of driver seat. Class ABC.	11

Paint

Paint color number.	0
N97020 A - L0006 WHITE	
N97200 FRAME N0001 BLACK	
N97700 BUMPER L0006 WHITE	
Bumper Painted Color A	0
Day Cab Standard Paint	0
1 - Color Paint - Day Cab Color will be White L0006EB if no other color is specified.	0
Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

Total Weight	10470
---------------------	-------

Prices and Specifications Subject to Change Without Notice.

Printed:	10/30/2015 2:25:41 PM	Complete	Model Number:	T300 Series Conventional
Effective Date:	Jul 1, 2015		Quote/DTPO/CO:	Q81518427
Prepared by:	Randy Smartt		Version Number:	36.22